

Datasheet for SwelFlex Cable 0,1kV

Type: **RKKJ 4X6+6**

6 mm², flexible, Conductor acc. to IEC 60228,5			
Properties	Nominal value	Tolerance	Unit
Wires in conductor, bare	75	-	Pcs.
Wire diameter	0,30	± 0,02	mm
Resistance	3,30	+0,06	Ω/Km
Lay length	<120	-	mm
Copper weight	50	-	Kg/km

Insulation of 6mm² acc. to ISO 6722			
Properties	Nominal value	Tolerance	Unit
Material	TI1	-	-
Temperature range	-40 till +70		°C
Wall thickness	0,5	+ 0,2	mm
Outer diameter	4,2	+ 0,4	mm
Colour	2*Red and 2*Blue		

Laying up of cores			
Properties	Nominal value	Tolerance	Unit
Lay Length	160	-50	mm
Helical lapping tape	20		mm
Dummy lead	1 of ø2mm		

Inner sheet			
Properties	Nominal value	Tolerance	Unit
Material	PVC	-	-
Wall thickness	0,5	+0,30	mm
Outer diameter	12,8	+ 0,60	mm
Colour	Natural		

SWEL AB
Ledjavägen 1
370 34 Holmsjö, Sweden
Telefon: +46 455 91167
Fax: +46 455 91359

www.swel.se
info@swel.se

SWELAB[®]
SWEDEN EAST EUROPEAN EL

Earth shielding			
Properties	Nominal value	Tolerance	Unit
Bare CU-wires	15	-	-
Wire diameter	0,8		mm
Binding	Helical tape		

UV-resistant outer sheet acc. to HD 603 S1			
Properties	Nominal value	Tolerance	Unit
Material	TII	-	-
Temperature range	-40 till +70		°C
Wall thickness	1,5	+0,25	mm
Outer diameter	15,8	+ 0,50	mm
Colour	Black		

Specific properties			
Properties	Nominal value	Unit	Standard
Voltage range	0,1	kV	
Test voltage, 5 min.	2.000	V	IEC 811
Drum size, flange	800	mm	
Length on each drum	500	m	
Weight on each drum	235	kg	

